



SLIM CASSETTE - 900×900 38QUS/42QTD-D8S



- **360° luchtstroom:** garandeert een gelijkmatige temperatuurverdeling in de ruimte.
- **Verse luchtinlaat:** de binnenunit heeft de mogelijkheid voor het aansluiten van verse ventilatielucht.
- **Geïntegreerde condenspomp:** de condenspomp heeft een opvoerhoogte van 1000 mm.

WIFI MODULE**



ENERGY CLASS



ULTRA-QUIET



AUTO-DIAGNOSIS SYSTEM



RESTART FUNCTION



AUTO SWING



R32



SLEEP MODE



INVERTER TECHNOLOGY



voorbereid**



FOLLOW ME



WEEKLY TIMER



AIR FLOW 360°



INDEPENDENT DEHUMIDIFICATION



LOUVER POSITION MEMORY



REFRIGERANT LEAK DETECTION



EASY INSTALLATION



Inclusief R667N



Optioneel KJR-120G2



OUTDOOR UNIT

38QUS024D8S

Cooling Capacity	kW	7.05 (3.20~7.90)
Heating Capacity	kW	7.20 (2.80~8.80)
Heating Capacity to -7 °C	kW	5.40
Heating Capacity to -10 °C	kW	5.00
Heating Capacity to -15 °C	kW	3.70
P design capacity cooling	kW	7.05
P design capacity heating (warmer)	kW	5.30
P design capacity heating (average)	kW	5.90
Temp. range (Cooling)	°C	-15~50
Temp. range (Heating)	°C	-15~24
SEER / SCOP (warm season) / SCOP (mid-season)	W/W	6.1 / 4.0 / 5.1
Energy label	-	A++ / A+ / A+++
Yearly energy consumption	kWh	405 / 1855 / 1620
EER/COP	W/W	2.95 / 3.93
Power supply	V-Hz	220~240V, 50Hz
Standard current draw (Cooling)	A	9.9
Standard input draw (Cooling)	W	2180
Standard current draw (Heating)	A	8.4
Standard input draw (Heating)	W	1830
Rated current	A	13.5
Rated input	W	2950
Refrigerant amount (R32)	kg	1.50
Liquid sid/Gas side	inch	3/8" / 5/8"
Standard piping length	m	5
Min. piping length	m	3
Max. piping length	m	50
Max. difference	m	25
Additional charge	g/m	24
Sound power level	dB(A)*	67
Sound pressure level	dB(A)*	61
Air flow	m³/h	2700
Weight (net/gross)	kg	49.5 / 53.0
Dimensions (LxWxH)	mm	845x363x702

INDOOR UNIT

42QTD024D8S

Indoor fan motor Input	W	141
Indoor fan motor max current	A	0.80
Sound power level	dB(A)*	61
Sound pressure level (Min.-Max)	dB(A)*	40~46
Air flow (Min.-Max)	m³/h	1030~1380
Panel weight (net/gross)	kg	6.0 / 9.0
Unit weight (net/gross)	kg	24.0 / 28.0
Panel dimensions (LxWxH)	mm	950x950x55
Unit dimensions (LxWxH)	mm	840x840x245
Paneel 4-weg cassette 40CAS-L5	900x900	

* Gemeten op 1 meter afstand van de bron

Als gevolg van ons beleid van voortdurende productverbetering kunnen de hierboven vermelde kenmerken en gegevens zonder voorafgaande kennisgeving worden gewijzigd. De afbeeldingen van producten en accessoires zijn indicatief.

LIGHT COMMERCIAL SOLUTIONS SLIM CASSETTE

SLIM CASSETTE 38QUS/42QTD-D8S



WiFi voorbereid**



OUTDOOR UNIT		38QUS036D8S	38QUS036D8T
Cooling Capacity	kW	10.50 (3.90~10.60)	10.50 (4.00~10.70)
Heating Capacity	kW	10.60 (2.90~13.50)	10.80 (2.90~14.10)
Heating Capacity to -7 °C	kW	9.70	9.60
Heating Capacity to -10 °C	kW	8.30	8.20
Heating Capacity to -15 °C	kW	8.20	8.10
P design capacity cooling	kW	10.50	10.50
P design capacity heating (warmer)	kW	8.70	8.10
P design capacity heating (average)	kW	10.50	10.50
Temp. range (Cooling)	°C	-15~50	-15~50
Temp. range (Heating)	°C	-15~24	-15~24
SEER / SCOP (warm season) / SCOP (mid-season)	W/W	6.1 / 4.0 / 4.9	6.1 / 4.0 / 4.9
Energy label	-	A++ / A+ / A++	A++ / A+ / A++
Yearly energy consumption	kWh	602 / 3045 / 3000	602 / 2835 / 3000
EER/COP	W/W	2.61 / 3.53	2.80 / 3.71
Power supply	V-Hz	220~240V, 50Hz	380~415V, 50Hz
Standard current draw (Cooling)	A	16.5	6.6
Standard input draw (Cooling)	W	3740	3950
Standard current draw (Heating)	A	13.3	5.0
Standard input draw (Heating)	W	2970	2910
Rated current	A	21.5	10.0
Rated input	W	4700	5600
Refrigerant amount (R32)	kg	2.40	2.40
Liquid sid/Gas side	inch	3/8" / 5/8"	3/8" / 5/8"
Standard piping length	m	5	5
Min. piping length	m	3	3
Max. piping length	m	65	65
Max. difference	m	30	30
Additional charge	g/m	24	24
Sound power level	dB(A)*	69	69
Sound pressure level	dB(A)*	64	64
Air flow	m³/h	4000	4000
Weight (net/gross)	kg	67.0 / 73.5	81.5 / 87.0
Dimensions (LxWxH)	mm	946×410×810	946×410×810
INDOOR UNIT		42QTD036D8S	42QTD036D8S
ECR artikelnummer			
Bruto prijs			
Indoor fan motor Input	W	141	141
Indoor fan motor max current	A	0.80	0.80
Sound power level	dB(A)*	62	62
Sound pressure level (Min.~Max)	dB(A)*	46~51	46~51
Air flow (Min.~Max)	m³/h	1440~1770	1440~1770
Panel weight (net/gross)	kg	6.0 / 9.0	6.0 / 9.0
Unit weight (net/gross)	kg	27.5 / 31.0	27.5 / 31.0
Panel dimensions (LxWxH)	mm	950×950×55	950×950×55
Unit dimensions (LxWxH)	mm	840×840×245	840×840×245
PANEEL 4-WEG CASSETTE 40CAS-L5	42QTD/36/48/60	900×900	



OUTDOOR UNIT		38QUS048D8T	38QUS060D8T
Cooling Capacity	kW	14.00 (4.70~14.60)	15.40 (5.20~16.70)
Heating Capacity	kW	15.60 (3.90~16.80)	18.00 (4.30~19.30)
Heating Capacity to -7 °C	kW	10.50	12.20
Heating Capacity to -10 °C	kW	10.00	11.90
Heating Capacity to -15 °C	kW	8.50	9.80
P design capacity cooling	kW	14.00	15.40
P design capacity heating (warmer)	kW	11.00	11.80
P design capacity heating (average)	kW	11.80	12.30
Temp. range (Cooling)	°C	-15~50	-15~50
Temp. range (Heating)	°C	-15~24	-15~24
SEER / SCOP (warm season) / SCOP (mid-season)	W/W	6.1 / 4.0 / 4.6	6.1 / 4.0 / 5.1
Energy label	-	A++ / A+ / A++	A++ / A+ / A+++
Yearly energy consumption	kWh	803 / 3850 / 3591	884 / 4130 / 3376
EER/COP	W/W	2.72 / 3.10	2.53 / 2.94
Power supply	V-Hz	380~415V, 50Hz	380~415V, 50Hz
Standard current draw (Cooling)	A	9.2	10.2
Standard input draw (Cooling)	W	5150	6080
Standard current draw (Heating)	A	8.2	10.3
Standard input draw (Heating)	W	5040	6130
Rated current	A	11.2	14.0
Rated input	W	6200	7500
Refrigerant amount (R32)	kg	2.80	2.95
Liquid sid/Gas side	inch	3/8" / 5/8"	3/8" / 5/8"
Standard piping length	m	5	5
Min. piping length	m	3	3
Max. piping length	m	65	65
Max. difference	m	30	30
Additional charge	g/m	24	24
Sound power level	dB(A)*	75	77
Sound pressure level	dB(A)*	66	66
Air flow	m³/h	7500	7500
Weight (net/gross)	kg	107.0 / 120.0	112.0 / 125.0
Dimensions (LxWxH)	mm	952×415×1333	952×415×1333

INDOOR UNIT		42QTD048D8S	42QTD060D8S
Indoor fan motor Input	W	141	232
Indoor fan motor max current	A	0.80	1.92
Sound power level	dB(A)*	65	65
Sound pressure level (Min.~Max)	dB(A)*	49~52	48~53
Air flow (Min.~Max)	m³/h	1380~1720	1540~1970
Panel weight (net/gross)	kg	6.0 / 9.0	6.0 / 9.0
Unit weight (net/gross)	kg	29.0 / 33.0	29.0 / 33.0
Panel dimensions (LxWxH)	mm	950×950×55	950×950×55
Unit dimensions (LxWxH)	mm	840×840×287	840×840×287

WIFI MODULE**		42QTD/36/48/60
---------------	--	----------------

* Gemeten op 1 meter afstand van de bron
 Als gevolg van ons beleid van voortdurende productverbetering kunnen de hierboven vermelde kenmerken en gegevens zonder voorafgaande kennisgeving worden gewijzigd. De afbeeldingen van producten en accessoires zijn indicatief.